
Features









Grooved Piping

Wide & Long Airflow

Anti-rust

Powerful Cool

Technical Specifications

Type (Cooling)	Performance Para
Indoor Unit	Capacity (Tr)
MS-GK13VA	Star Rating - As Pe
Outdoor Unit	
MU-GK13VA	Power Supply
	Capacity (Rated)

Performance Parameters	
Capacity (Tr)	1 Tr
Star Rating - As Per BEE	2 Star POWER SAVINGS GUIDE
Power Supply	230 V / 50 Hz / Single Phase
Capacity (Rated)	3.6kW
Total Input (Rated)	1.000kW
EER	3.60
Operating Current (Amps)	4.5
Air Volume Indoor Unit(CFM)	477

Dimensions & Weight				
Indoor unit	Dimensions (H x W x D)	mm	290x799x232	
	Weight	kg	10	
	Dimensions (H x W x D)	mm	525x718x255	
Outdoor unit	Weight	kg	33.5	
	Breaker Size (MCB required)	Α	10	
Ext.Piping	Diameter Liquid	mm (inches)	6.35	
	Diameter Gas	mm (inches)	12.7	
	Max.Length Out-In	m	20	
	Max.Height Out-In	m	10	

Compressor, Refrigerant & Ambient Operations		
Sound Level (SPL) Indoor Unit(Low- Mid-Hi-SHi) dB(A)	29/36/42/46	
Refrigerant	R410A R410A OZONE	

