

Features



50 degree operating Range (Except MS-GS10)



HIGH CFM 777- CMH 1320 (MS-GS18)



Micro Particle Catching Filter(Optional Part)



Powerful Cool

Technical Specifications

Type (Cooling)		Performance Parameters		Compressor, Refrigerant & Ambient Operations			
Indoor Unit		Capacity (Tr)	1.0 Tr	SPL Indoor Unit(Silent-Low-Mid-Hi-SHi) dB(A)	29/37/42/47		
MS-GS13VF		Star Rating - As Per BEE	2 Star 	Refrigerant	R32 		
Outdoor Unit		Power Supply	230 V / 50 Hz / Single Phase				
MU-GS13VF		Capacity (Rated)	3.6 kW				
		Total Input (Rated)	1.02 kW				
		ISEER	3.53				
		Operating Current Rated(A)	4.6				
		Air Volume (CFM) Indoor Unit(Silent-Low-Mid-Hi-SHi)	251/270/340/408				
Dimensions & Weight							
Indoor unit	Dimensions (H x W x D)	mm	290x799x232				
	Weight	kg	9.5				
Outdoor unit	Dimensions (H x W x D)	mm	525x718x255				
	Weight	kg	34.0				
Ext.Piping	Diameter Liquid	mm (inches)	6.35(1/4)				
	Diameter Gas	mm (inches)	9.52(3/8)				
	Max.Length Out-In	m	20				
	Max.Height Out-In	m	10				

