

Features



Auto Restart



Joint Lap DC Motor



Magnetic Flux Vector
Sine Wave Drive



Heat Caulking Fixing
Method

Technical Specifications

Type (Cooling)		Performance Parameters				Compressor, Refrigerant & Ambient Operations		
Indoor Unit		Capacity (Tr)		1 Tr		SPL Indoor Unit dB(A) (Silent/Low/Mid/High/SHi)		19/24/31/38/43
MSY-GR13VF-DA1		Star Rating - As Per BEE		5 Star 		Refrigerant		R32 
Outdoor Unit		Power Supply		230 V / 50 Hz / Single Phase				
MUY-GR13VF-DA1		Capacity (Rated Min-Max)		3.7(1.4-4.1)kW				
		Total Input (Rated Min-Max)		1.01(0.32-1.31)kW				
		ISEER		5.02				
		Operating Current (A)		4.8				
		Air Volume (CFM) Indoor Unit(Silent/Low/Mid/High/SHi)		152/187/254/335/445				
Dimensions & Weight								
Indoor unit	Dimensions (H x W x D)	mm	280x838x229					
	Weight	kg	10					
Outdoor unit	Dimensions (H x W x D)	mm	538x699x249					
	Weight	kg	24.5					
Ext.Piping	Diameter Liquid	mm (inches)	6.35(1/4)					
	Diameter Gas	mm (inches)	9.52(3/8)					
	Max.Length Out-In	m	20					
	Max.Height Out-In	m	12					

