

Features



LCD Remote Control



Computerized Dehumidification





New LEV Control



Joint Lap DC Motor

Technical Specifications

Type (Cooling)		Performance Parameters				Compressor, Refrigerant & Ambient Operations		
Indoor Unit		Capacity (Tr)		1 Tr		SPL Indoor Unit(Low/Mid/High/SHi) In dB(A)-Cooling		22/31/38/45
MSZ-HP13VA		Star Rating - As Per BEE		2 Star 		SPL Indoor Unit(Low/Mid/High/SHi) In dB(A)-Heating		23/30/37/44
Outdoor Unit		Power Supply		230 V / 50 Hz / Single Phase		Refrigerant		R410A 
		Cooling Capacity (Rated Min-Max)		3.15(1.4-3.50)kW				
		Heating Capacity (Rated Min-Max)		3.60(1.1-4.10)kW				
		Total Input (Rated Min-Max)-Cooling		1.04(0.36-1.27)kW				
		Total Input (Rated Min-Max)-Heating		0.995(0.37-1.2)kW				
		ISEER		3.62				
		Operating Current (Rated)-Cooling		5.1(A)				
		Operating Current (Rated)-Heating		4.7(A)				
		Air Volume (CFM) Indoor Unit(Low/Mid/High/SHi)-Cooling		134/204/278/386				
Air Volume (CFM) Indoor Unit(Low/Mid/High/SHi)-Heating		122/195/270/366						
Dimensions & Weight								
Indoor unit	Dimensions (H x W x D)	mm	290x799x232					
	Weight	kg	9					
Outdoor unit	Dimensions (H x W x D)	mm	538x699x249					
	Weight	kg	25.0					
	Breaker Size (MCB required)	A	10					
Ext.Piping	Diameter Liquid	mm (inches)	6.35(1/4)					
	Diameter Gas	mm (inches)	9.52(3/8)					
	Max.Length Out-In	m	20					
	Max.Height Out-In	m	12					

